



GENERAL MONITORS
Protection for life.

MODEL TA102A

Single-Channel Combustible Gas Trip Amplifier Module



Features

- RS-485 Serial Communications
- Digital Display
- LED Status Indication
- Relay, Open Collector Alarm & Fault Outputs
- User Setup, Setup Check Modes
- Live Insertable into Rack
- Password Option

Benefits

- Remote set-up and interrogation via General Monitors' Model CC02A Communications module
- Provides visual indication of alarm status and setup cues
- Provides visual indication of fault and status
- Multiple outputs for multi-function use
- Configuration easy to set up or change
- Ease of maintenance
- Tamper-proof operation

Description

The General Monitors Model TA102A is a single-channel Combustible Gas Trip Amplifier Module designed to monitor combustible gases and vapors within the lower explosive limit (LEL) and provide status indication and alarm outputs.

Microprocessor-based electronics allow all options to be user selectable through front panel interface (mode/select switch and digital display). A digital display on the TA102A indicates fault codes and set up options. Other features of the TA102A are LED indications of status, as well as both open collector and relay outputs for fault, low alarm and high alarm.

Each module has RS-485 serial communications providing an interface with a General Monitors Model CC02A MODBUS communications module. Fault and alarm status, as well as setup options, can be configured via the CC02A module.

The TA102A is part of the Zero Two Series Gas and Fire Detection System which is a flexible solution for various combustible, toxic gas and fire detection applications. All of the Zero Two Series system cards are compatible and can be intermixed within the same rack if required. The Zero Two Series Rack includes options of 4, 8 or 16 channels and provides a bus of common terminals to each channel.

Applications

- Refineries
- Drilling Platforms and Rigs
- Gas Collection and Distribution Facilities
- Gas and Oil Production Platforms
- LPG/LNG Processing and Storage
- Solvent Vapors
- Chemical Plants
- Wastewater Treatment Facilities



MODEL TA102A

System Specifications

Detector Type:	General Monitors Intelligent Sensor using catalytic oxidation or infrared detector technology
Measuring Ranges:	0-100% LEL
Front Panel Indicators:	A1 - Warning A2 - Alarm CAL - Calibration/Check READY - Normal Operation FAULT - Malfunction SETUP - User Options/Check DISPLAY - 2x7 Segment
Test Features:	Power on - Electronic Integrity Card - Functionality & Alarm Ramp LED - Integrity of LED's & Display
Modes:	Setup, Setup Check & Inhibit outputs
Password:	Prevents unauthorized alteration of setup parameters (can be disabled)
Classification:	General purpose, non-hazardous areas
Warranty:	Two years
Approvals:	CSA, CE Marking, GOST SIL 2 suitable

Environmental Specifications

Operating Temperature Range:	0°F to +150°F (-18°C to +66°C)
Storage Temperature Range:	-40°F to +150°F (-40°C to +66°C)
Humidity:	5% to 100% RH, non-condensing
EMC Susceptibility:	10V/m max.

Mechanical Specifications

Length:	9.9 inches (251mm)
Height:	6.8 inches (173mm)
Width:	1.0 inch (25mm)
Weight:	11.2 ounces (318 grams)

Electrical Specifications

Power:	20-36 VDC @ 475mA max., including Intelligent Sensor
Input Impedance:	30 Ohms
Relay Ratings:	4A @ 250 VAC / 30V RMS/42.4 peak, 3A @ 30 VDC, resistive max. A1, A2 - DPDT Fault - SPDT
Analog Signal:	0 - 20mA (300 Ohms max. load) Malfunction - 0mA Calib/Setup/Check - 1.5mA Beam Block - 2.0mA 0-100% LEL - 4-20mA Over-range - 20-22mA
Open Collector Ratings:	100mA @ 35 VDC max. A1, A2, Fault, LA1, LA2, CAL, FUA, UA
Cable Requirements:	3 wire shielded cable. Max. allowable distance between Smart Sensor & TA102A @ 24 VDC nominal: 14AWG - 4500 ft. (1372m) Max. allowable distance for analog output (300 Ohms loop resistance max. between AO+ and AO-): 14AWG - 9000 ft. (2740m)
Standard Configuration:	TA102A-2-1-1-1-1 Latch alarm, non-latch warn de-energized, 3 sec. ramp time, relays inhibited

Specifications subject to change without notice.

Represented by:

General Monitors Worldwide



www.generalmonitors.com

Lake Forest, CA

26776 Simpatica Circle
Lake Forest, California 92630
Tel: +1-949-581-4464
Fax: +1-949-581-1151
Email: info@generalmonitors.com

Houston, TX

9776 Whithorn Drive
Houston, Texas 77095
Tel: +1-281-855-6000
Fax: +1-281-855-3290
Email: gmhou@generalmonitors.com

Ireland

Ballybrit Business Park
Galway
Republic of Ireland
Tel: +353-91-751175
Fax: +353-91-751317
Email: info@gmil.ie

Singapore

No. 2 Kallang Pudding Road
#09-16 Mactech Building
Singapore 349307
Tel: +65-6748-3488
Fax: +65-6748-1911
Email: genmon@gmpacifica.com.sg

United Arab Emirates

P.O. Box 61209
Jebel Ali
Dubai
United Arab Emirates
Tel: +971-4-8815751
Fax: +971-4-8817927
Email: gmme@emirates.net.ae

United Kingdom

Heather Close
Lyme Green Business Park
Macclesfield, Cheshire
United Kingdom, SK11 0LR
Tel: +44-1625-619583
Fax: +44-1625-619098
Email: info@generalmonitors.co.uk